




















ROMEX® product overview

pavement jointing mortars, auxiliary products and displacement protection

	Product	Optimum areas of application	Joint width	Joint depth	Load class	Water permeability	Containers	Page
Private sector	ROMPOX® - JOINTING SAND NP	<ul style="list-style-type: none"> For tightly laid paving stones Interlocking paving Driveways 	≥ 1 mm 1/16"	≥ 30 mm 1 1/4"	 All load classes	Permeable	25 kg 55.12 lb bag	24–25
	ROMPOX® - EASY	<ul style="list-style-type: none"> Patio, Garden path For coated and sensitive stone surfaces 	≥ 5 mm 1/4" narrower joints can be jointed but with increased work	≥ 30 mm 1 1/4"	 Light traffic loads up to 3.5 tons	Highly water permeable	15 kg 33.07 lb bucket, 25 kg 55.12 lb bucket	26–27
	ROMPOX® - POWER JOINT	<ul style="list-style-type: none"> Paved stone surfaces with traffic loads 	≥ 8 mm 3/8" narrower joints can be jointed but with increased work	≥ 30 mm 1 1/4"	 Medium traffic loads up to 7.5 tons	Permeable	25 kg 55.12 lb bucket	28–29
	ROMPOX® - PATIO	<ul style="list-style-type: none"> Sensitive stones Coated stone surfaces 	≥ 5 mm 1/4"	≥ 30 mm 1 1/4"	 Light traffic loads up to 3.5 tons	Highly water permeable	25 kg 55.12 lb bucket	30–31
	ROMPOX® - DRAIN	<ul style="list-style-type: none"> Driveways, parking space 	≥ 5 mm 1/4"	≥ 30 mm 1 1/4"	 Light traffic loads up to 3.5 tons	Highly water permeable	26.8 kg 59.08 lb bag	32–33
	ROMPOX® - DRAIN PLUS	<ul style="list-style-type: none"> Driveways, parking space 	≥ 5 mm 1/4"	≥ 30 mm 1 1/4"	 Light traffic loads up to 3.5 tons	Highly water permeable	26.5 kg 58.42 lb bag, 25 kg 55.12 lb bucket	34–35
	ROMPOX® - D1	<ul style="list-style-type: none"> Polygonal slabs Driveways, parking space 	≥ 3 mm 1/8"	≥ 30 mm 1 1/4"	 Medium traffic loads up to 7.5 tons	Highly water permeable	27.5 kg 60.63 lb bag, 12.5 kg 27.56 lb bucket, 25 kg 55.12 lb bucket	36–37
	ROMPOX® - FLEX-LIGHT	<ul style="list-style-type: none"> Unbonded surfaces around the house subject to heavy loads 	≥ 5 mm 1/4"	≥ 30 mm 1 1/4"	 Medium traffic loads up to 7.5 tons	Highly water permeable	25 kg 55.12 lb bucket	42–43
	ROMPOX® - JOINT STRENGTHENER	<ul style="list-style-type: none"> Coated concrete and natural stones as well as clinker surfaces 	≥ 1 mm 1/16"	≥ 30 mm 1 1/4"	 Light traffic loads up to 3 tons	Highly water permeable	1 Ltr. 0.26 gal bottle, 5 Ltr. 1.32 gal canister, 10 Ltr. 2.64 gal canister	44–45
	ROMPOX® - D7000	<ul style="list-style-type: none"> For pathways and commercial surfaces 	–		 Light traffic loads up to 3 tons	Very high water permeable	20 Ltr. 5.28 gal canister	46–47
	ROMPOX® - DEKO	<ul style="list-style-type: none"> Suitable for light grit/gravel 	surface depth ≥ 30 mm 1 1/4"		 Light traffic loads up to 3 tons	Very high water permeable*	1 kg 2.2 lb tin, 30 kg 66.14 lb bucket	130–131
	ROMPOX® - DEKOFIX	<ul style="list-style-type: none"> for light wells, spray strips, private tree surrounds, non loadbearing decorative surfaces, graves and unused surfaces 	surface depth ≥ 20 mm		–	Highly water permeable	25 kg 55.12 lb bucket	132–133
Public sector	ROMPOX® - FLEX-JOINT	<ul style="list-style-type: none"> Unbonded surfaces in the public sector subject to heavy loads 	≥ 5 mm 1/4"	in case of traffic loads 2/3 of stone height	 Medium to heavy, up to 25 t in combination with ground anchors	Highly water permeable	25 kg 55.12 lb bucket	50–51
	ROMPOX® - D2000	<ul style="list-style-type: none"> Public paved stone surfaces 	≥ 5 mm 1/4"	≥ 30 mm 1 1/4"	 Medium to heavy (up to 25 t)	Permeable	27.5 kg 60.63 lb bag	52–53
	ROMPOX® - D3000	<ul style="list-style-type: none"> Suitable for repairing broken cement surfaces 	≥ 3 mm 1/8"	≥ 10 mm 3/8" Depth of joint crack	 Medium to heavy (up to 25 t)	Highly water permeable	27.5 kg 60.63 lb bag	56–57
	ROMPOX® - TRAFFIC V2	<ul style="list-style-type: none"> Public surfaces with heavy loads 	≥ 8 mm 3/8"	≥ 30 mm 1 1/4"	 Heaviest loads (up to 40 t)	Permeable	28 kg 61.73 lb bag	64–65
	ROMPOX® - D4000 HR	<ul style="list-style-type: none"> Renovation, repair of public areas 	surface depth ≥ 10 mm 3/8"		 Heaviest loads (up to 40 t)	–	17.5 kg 38.58 lb bucket	140–141
	ROMPOX® - PROFI-DEKO	<ul style="list-style-type: none"> Path construction, tree surrounds Suitable for dark grit/gravel 	surface depth ≥ 30 mm 1 1/4"		 Light traffic loads up to 3 tons	Very high water permeable*	3 kg 6.62 lb container, 30 kg 66.14 lb bucket	134–135
	ISAT®c DISPLACEMENT PROTECTION	<ul style="list-style-type: none"> Public sector 	As described in the leaflet for surface fastenings with large formats (MFG issue 2013).		 Heaviest loads (up to 40 t)	–	–	146–161
Auxiliary products	ROMPOX® - TRASS-BED-COMPOUND	<ul style="list-style-type: none"> Private and public sector 	≥ 30 mm 1 1/4" layer thickness		 Heaviest loads (up to 40 t)	Highly water permeable	40 kg 88.18 lb bag, 25 kg 55.12 lb bag (Compound)	118–119
	ROMPOX® - ADHESION ELUTRIANT	<ul style="list-style-type: none"> Private and public sector 	≥ 3 mm 1/8" layer thickness		Heaviest loads (up to 40 t)	–	25 kg 55.12 lb bag	120–121

* depending on grain size